

## PL\_CALOR\_TPRS-S 125 PIPE

HOSES › Chemical hoses

Very flexible hose made of extruded sheet of THERMOPLASTIC POLYOLEFIN elastomer with flame retardant additives and incorporated spring steel spiral, sheet thickness 0.80.

Particularly smooth internal surface. Indicated in the presence of aggressive fumes.


Excellent quality-price compromise for the passage of hot fumes. Black colour.

**Operating temperature: -20° +125°C (135° maximum peak for a few minutes)**

Standard length 10 meters

on request rolls up to 20 meters up to Ø 200 mm

otherwise length 6 meters for larger diameters Ø 600 and Ø 700.



Mastertubi.it/q?374

| Code          | Diameters mm | Operating pressure bar | Vacuum bar | Curvature radius mm | Weight gr/m |
|---------------|--------------|------------------------|------------|---------------------|-------------|
| 11PVCA0000040 | 40           | 0.5                    | 0.25       | 28                  | 228         |
| 11PVCA0000050 | 50           | 0.4                    | 0.20       | 35                  | 295         |
| 11PVCA0000060 | 60           | 0.4                    | 0.16       | 42                  | 342         |
| 11PVCA0000070 | 70           | 0.35                   | 0.14       | 49                  | 339         |
| 11PVCA0000080 | 80           | 0.28                   | 0.10       | 56                  | 456         |
| 11PVCA0000090 | 90           | 0.24                   | 0.09       | 64                  | 428         |
| 11PVCA0000100 | 100          | 0.2                    | 0.09       | 70                  | 515         |
| 11PVCA0000120 | 120          | 0.2                    | 0.08       | 80                  | 610         |
| 11PVCA0000130 | 130          | 0.20                   | 0.08       | 90                  | 684         |
| 11PVCA0000150 | 150          | 0.10                   | 0.06       | 105                 | 772         |
| 11PVCA0000160 | 160          | 0.10                   | 0.06       | 110                 | 850         |
| 11PVCA0000180 | 180          | 0.09                   | 0.05       | 128                 | 935         |
| 11PVCA0000200 | 200          | 0.08                   | 0.05       | 140                 | 1024        |

|               |     |      |      |     |      |
|---------------|-----|------|------|-----|------|
| 11PVCA0000250 | 250 | 0.05 | 0.04 | 175 | 1280 |
| 11PVCA0000300 | 300 | 0.03 | 0.03 | 210 | 1540 |
| 11PVCA0000350 | 350 | 0.02 | 0.02 | 245 | 2340 |
| 11PVCA0000400 | 400 | 0.02 | 0.02 | 280 | 2630 |
| 11PVCA0000450 | 450 | 0.01 | 0.01 | 315 | 2960 |
| 11PVCA0000500 | 500 | 0.01 | 0.01 | 350 | 3290 |