

PU WIND HOSE/Heavy - antistatic

HOSES › Dust and chip suction polyurethane hoses

Ester-based polyurethane hose with shock-proof rigid PVC reinforcement spiral covered with polyurethane. Copper cable inserted for the dispersion of surface electric currents. The internal surface is entirely smooth while the external one is corrugated to make the hose flexible to handle.

The ANTISTATIC version includes the cable of 9 copper wires covered with PU on the external surface parallel to the reinforcing coil.

Also available in the non-antistatic version (without incorporated copper wire)

Operating temperature: -40°C +80°C

Color: transparent with gray spiral.

Use: suction of abrasive dust, shavings, plastic granulate.

Polyurethane leaf thickness from Ø 40 to Ø 150 thickness 1mm



Code	Diameters mm	Weight g/m	mH2O depression	Radius of curvature	Rolls m
11PVPUATPMA038	38.1x45.7	310	3	130	30
11PVPUATPPA040	40x47	350	3	140	30
11PVPUATPPA045	45x52.6	445	3	160	30
11PVPUATPPA052	50.8x59.4	550	3	175	30
11PVPUATPPA060	60x68.6	640	3	200	30
11PVPUATPPA0630	63.5x71.9	670	3	230	30
11PVPUATPPA065	65x73.4	680	3	230	30
11PVPUATPPA070	70x79.4	750	3	250	30
11PVPUATPPA076	76.2x85.6	810	2.5	270	30
11PVPUATPPA080	80x90.4	900	2.5	290	30
11PVPUATPPA090	90x100.6	1050	2.5	360	30
11PVPUATPPA100	100x111.4	1290	2.5	400	30
11PVPUATPPA120	120x132	1500	2.5	470	30