

WALL HYDRANT CE76

FITTINGS FOR AGRICULTURAL-INDUSTRIAL MAINTENANCE › FIRE FIGHTING ITEMS › WALL HYDRANTS CE
UNI EN 671/2:2003

INDOOR/OUTDOOR WALL HYDRANT

Art. CE76 - UNI45 in accordance with UNI EN671/2 - Marked CE0497/CPR/134

Form ☐C☐ type 2, complete with:

- ☐ Wall box in electro-galvanised steel painted red RAL 3000 based on polyester resins, resistant to corrosion in accordance with ISO 9227, door with butterfly handle including seal, anti-wasp ventilation slots and provision for hole.
- ☐ Transparent ☐INTEGRA☐ unbreakable sheet, complete with instructions for use.
- ☐ DN45 flexible hose certified EN 14540, with UNI 804 fittings and UNI 7422 binding with rubber binding cover sleeves.
- ☐ Hose protection harness in red plastic material.
- ☐ 1 ¹/₂ hydrant tap with thread compliant with ISO 7-1.
- ☐ Jet regulation lance.
- ☐ Assembly instructions.
- ☐ CE mark identification code sticker.

DN45 PN16 HOSES: 15 m, 20 m, 25 m, 30 m

Available on request without glass.

Rounded corners - New opening system, door without hinges.



Mastertubi.it/q?742