

FOREST FIRE HOSE EN 1947

FITTINGS FOR AGRICULTURAL-INDUSTRIAL MAINTENANCE › FIRE FIGHTING ITEMS › HOSES FOR FOREST FI

Fire hose compliant with EN 1947, reelable, robust and flexible, resistant to abrasion and fire-fighting foams.

Standards: EN 1947:2014 type C, class 1, category 2.

Application: cord hose for delivering water and fire-fighting liquids, which can be up on a reel, robust and flexible, designed for service on fire engines.

Temperature: -20°C to +60°C.

Marking: embossed ribbon "IVG EN 1947:2014-2-C-1-DI-40 bar-quarter and year of manufacture".

Tube : black, smooth, EPDM rubber resistant to chemicals and firefighting foams.

Reinforcement : high resistance synthetic fabrics.

Cover : black, smooth (wrapped finish), EPDM rubber resistant to atmospheric agents and abrasion.

Code	Diameter Internal		Diameter External		Pressure Work		Pressure I explode		Weight Nominal		radius curvature		Length Max
													
	mm	inch	mm	inch	Cafe	psi	Cafe	psi	kg/m	lbs/ft	mm	inch	m
1432745	12	15/32	22	0.87	40	600	120	1800	0.29	0.20	200	7.9	120
1430610	19	3/4	32.5	1.28	40	600	120	1800	0.62	0.42	200	7.9	120
1422758	25	1	38.5	1.52	40	600	120	1800	0.76	0.51	200	7.9	120
1424351	33	1-19/64	45.5	1.79	40	600	120	1800	0.83	0.56	280	11.0	120