

PARTICULATE FILTER L20

AUTO GAS SUCTION EQUIPMENT > EHC PORTABLE FILTERS FOR INDUSTRIAL VEHICLES

FILTER FOR HEAVY VEHICLES - TRUCKS - BUS

The **L 20** filter is an exhaust gas purifier designed for the temporary driving of vehicles inside factories, boats, workshops and exhibition halls. The filter works immediately upon start-up and offers maximum flexibility inside and is not affected by moisture. The filter separates mutagenic, carcinogenic and allergic substances attached to the exhaust gas particles.

Particle separation	> 99.9%
Separation of aldehydes	~90%
Max. displacement	14 Liter Cyl.
Max. temperature	200°C
Filter life *	~ 150 starts
Weight:	5 / 7 kg

^{*} Life time depends on engine size, engine type, diesel quality, how the vehicle is used and the condition of the engine.



EHC P15 is approved on <u>VERT-</u> Filterlist B272 (CH) Swiss Federal Office for the Environment (FOEN), Federal Materials Testing and Research Laboratory (EMPA); GERMAN TECHNICAL INSPECTION ASSOCIATION (TÜV). The EHC particle filter can be disposed of as normal waste.







model	description	maximum temperature
4120528	filter, casing cartridge and by-pass complete with connection for flexible hose, 80mm hole	200°
4120983	filter, casing cartridge and by-pass complete with rigid connection for trucks, minimum muffler hole diameter 100mm	200°
4120171	replacement cartridge for L20 activated carbon, minimum pack of two pieces	300°
4120371	replacement cartridge for L20 without activated carbon, minimum pack of two pieces	200°
4121241	L20-P filter, casing cartridge and by-pass complete with pneumatic seal connection for trucks, hole from 70 to 120mm	200°
4121261	L20-P filter, casing cartridge and by-pass complete with pneumatic seal connection for trucks, hole from 106 to 150mm	200°
4120448	filter, casing cartridge and DOUBLE by-pass complete with connection for trucks, 80mm hole suitable for engines up to 35 liters	200°

















Mastertubi.it/q?774