

SAE J20 R3 WIRED SILICONE

HOSES › Silicone rubber hoses and sleeves

SAE J20 R3 blue silicone screened hose

It is a quality silicone hose that meets the operational requirements of SAE J20 R3 Class A (TMP RP303B Class I, grade 2).

Prolonged flexibility even after long exposure to extreme temperatures, severe weather conditions or exposure to ozone. This hose will remain soft and flexible after years of use unlike traditional rubber which will harden and crack. However silicone is not suitable for use in the presence of mineral oil, however it resists engine oil 'fog' found under normal operating conditions. For retail sale, this hose is available in 20m distribution boxes, maximum length produced 76 metres. For higher temperatures, meta-aramid reinforcement (NOMEX) is available



Mastertubi.it/q?826

Construction: Blue Smooth Silicone Rubber with Reinforcement: High Strength Nylon Fiber.

Operating temperature: -60° +180° C

Use: connection of cooling systems with water and glycol, automotive industry.

DIAMETER INTERNAL	DIAMETER EXTERNAL	PRESSURE OF EXERCISE	PRESSURE BURST
mm - inch	mm - inch	Cafe	Cafe
6.30 - 1/4"	13.20 - 1/2"	9.60	28.80
7.90 - 1/3"	15.00 - 3/5"	8.80	26.50
9.50 - 3/8"	16.60 - 2/3"	7.70	11.00pm
12.70 - 1/2"	8.30pm - 4/5"	6.80	8.30pm

15.80 - 5/8"	24.50 - 1"	5.90	17.80
19.00 - 3/4"	27.90 - 1"	5.10	3.20pm
10.00pm - 7/8"	31.30 - 1"1/4	5.00	3.00pm
25.40 - 1"	34.50 - 1"1/3	4.90	14.80
28.00 - 1"1/8	38.00 - 1"1/2	4.40	1.20pm
32.00 - 1"1/4	43.00 - 1"2/3	3.90	11.80